# Product Overview

| | CPU | Memory | SSD | Interfaces | Operating Temp. | * optional or Please check Datasheet and Manual |
|---|---|---|---|---|---|---|

| Vendor | Formfactor | Product | CPU Vendor | Platform | Generation | CPU | Soldered CPU | Chipset | DDR3L | DDR4 | DDR5 | soldered onboard | SO-DIMM | DIMM-Socket | max. Size | soldered onboard | Standard SSD | Graphic | LVDS | eDP | MIPI-DSI | V-by-One | USB-C | USB 2.0 | USB 3.2 Gen1 (USB 3.0) | USB 3.2 Gen2 (USB 3.1) | USB 3.2 Gen2x2 | USB 4.0 | GbE Ethernet | 2.5 GbE Ethernet | RS232/422/485 | RS232 | UART | SATA | SATA Power | I2C or SMBus | GPIO | miniPCIe/mSATA | M.2 | Audio | HDA w. Aplifier | TPM | CAN | SPI | eSPI | SDIO | Printer (Parallel) port | PCIe x 16 | PCIe x 8 | PCIe x 4 | PCIe x 1 | PCI | DC-in | 0° ...+60°C | -20° ...+70°C | -25° ...+80°C | -40° ...+85°C | Others |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| The information contained in this document has been carefully researched and is, to the best of our knowledge, accurate. However, we assume no liability for any product failures or damages, immediate or consequential, resulting from the use of the information provided herein. Our products are not intended for use in systems in which failures of product could result in personal injury. All trademarks mentioned herein are property of their respective owners. All specifications are subject to change without notice. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | **Single-Board Computer** | | | | | | | | | | | | | | | | | | |